



- TERRACOTTA
- UNPOLISHED STONE AND AGGLOMERATES



WHAT IT'S FOR

- Protects and enhances internal floors.
- Protects from wear.
- Creates a barrier against water and oil stains.
- Excellent as a base coat on terracotta and rustic natural stone floors, prior to a wax finish.

ADVANTAGES

- Water based: it is environmentally friendly and requires a shorter treatment time as it can be applied to surfaces still not completely dry.
- Brings out the natural colour of the surface.
- Ideal for internal surfaces.

HOW IT'S USED

No dilution: ready to use

Application:

- 1 *Stir before use. Then spread evenly with a large brush or a fleece over a perfectly clean surface. Soak the joints thoroughly. Since it is a water-based product, residual humidity is permissible, so it can be applied just a few days after the initial cleaning.*
- 2 *On particularly porous terracotta surfaces, apply a second within 4 hours after the first.*
- 3 *After 4 hours, complete treatment with two coats of a FILAJET. Choose your finishing wax on the basis of the material, the final appearance required and the intended use of the floor.*

Maintenance:

diluted solution of FILACLEANER

COVERAGE

With one litre:

Terracotta Tuscan, rustic, polished	15/20 m²
Handmade Terracotta hollow tile, brick, spanish	7/10 m²
Stone	10/20 m²

"Coverage rates are approximate and refer to a single coat of the product"

Packaging

- 1 litre flasks in box of 12.
- 5 litre flasks in box of 4.

PRECAUTIONS

- Keep out of the reach of children.
- Dispose of the container properly after use.
- Product not frost resistant in container. Store at room temperature.

TEMPERATURE

Storage temperature: between 5° C and 30° C.
Must be applied to material at temperatures between 10° and 30° C.

COMPOSITION

Blend of siloxane emulsions and organic resins dispersed in water.

LABELLING

No risk or safety labels or warnings are required since the product is not classified as hazardous under current regulations.

According to the legislative decree 161/06.

High performance one component paints (floor coatings). EU limit value for this product (Cat: 1/i): 140 g/l (2007). This product contains max. 3 g/l.

TECHNICAL INFORMATION

Appearance: liquid
Colour: milky white
Odour: distinctive, resinous
Density: 1,001 kg/litre
pH: 8,0

The information above reflects our latest technical know-how and is the outcome of ongoing laboratory research and testing. However, some factors are beyond our control. It is essential to integrate our suggestions with your own on-site preliminary tests and check. Fila accepts no liability for improper use of its products.